

Plant & Equipment Specification

TIPPER LORRY (DELIVERIES & COLLECTIONS ONLY)

Ref: HSF-SP-0046HS Version: 2.0

Typical illustration



Core requirements

Tipper / Tipper Grab lorry up to 32t GVW, diesel engined, 6 or 8 wheel configuration undertaking deliveries & collection. It does not cover LCV vehicles

Environmental requirements

If registered post Dec '13, Engine minimum must comply with both EEV and Euro VI emission standards. Waste carriers licence.

Mandatory Requirements

Plant - general

- ✓ Must be compliant with EC Machinery Directive 2006/42/EC and supplied with a declaration of conformity
- ✓ Evidence of Pre-hire inspection
- ✓ Evidence of regular inspection plus "next service and or inspection due" date sticker
- ✓ Operator instructions must be with the machine
- ✓ All safety decals in place and legible

Plant - specific

- ✓ Public Highway compliance with C&U regulations – (VED registered, working Lights, indicators, registration plate's front & rear etc.)
- ✓ When delivering into traffic controlled areas, Chapter 8 compliant beacons, reflective chevrons and 'Highway/Motorway Maintenance' signage (as appropriate) must be in use
- ✓ Current Operator licence displayed
- ✓ Current MOT plating certificate
- ✓ Mirrors (including Class V & VI)/CCTV to satisfy 1m high at 1m distance 360° visibility criteria
- ✓ Seat belts must be fitted and operational
- ✓ Audible reversing alarm
- ✓ Locking doors with key
- ✓ Cab steps and handles painted high visibility yellow ensuring 3 points of contact is achievable
- ✓ Safe access for refuelling, maintenance and to any place where accessories stored
- ✓ Where access is required at height for security & maintenance purposes, suitable system must be in place to prevent falling from height
- ✓ Tipping linkage – must have no excessive play

If fitted with a grab/crane:

- ✓ 12 month thorough examination certificate for grab/crane
- ✓ 6 month thorough examination certificate on lifting accessories
- ✓ SWL to be clearly marked
- ✓ Load bearing hydraulic cylinders fitted with check valves
- ✓ Rear work lights
- ✓ Flashing lights on outrigger rams
- ✓ Boom above horizontal audible warning
- ✓ Spring assisted drop sides (if fitted)

Operator - general

- ✓ Attend full induction prior to starting work
- ✓ Be briefed on the site specific Plant, Vehicle and People Management Plan (PVPMP) and check for overhead obstructions and hazards
- ✓ Be signed onto the appropriate Safe System of Work documentation for the task
- ✓ Complete Pre-use check sheet/e-inspection
- ✓ Comply with Pre-use and Defect Reporting System
- ✓ Have a competency assessment prior to being put to work – be familiar with machine
- ✓ Report all unsafe conditions
- ✓ Abide by specific BB Company policies, procedures and permits
- ✓ Always operate/use the equipment in accordance with manufacturer's instructions / recommendations

Operator - specific

- ✓ Must have a current relevant driving licence if driving on the public highway
 - ✓ Shall hold a current Driver CPC qualification
 - ✓ Full site-defined PPE must be worn - loose fitting clothing should be avoided to prevent inadvertent operation of controls
 - ✓ Operator to mount and dismount machine using fixed access arrangements and always facing the machine using 3 points of contact
 - ✓ Seat belt must be worn (when driving)
 - ✓ Engine/power must be turned off if approached by others and keys removed from the ignition before leaving the cab unattended for any reason
 - ✓ Shall stop work if any unauthorised/unsupervised personnel enter their immediate work area
 - ✓ Do not elevate body whilst moving
 - ✓ All ancillary equipment and tools to be secured when tipping
 - ✓ Tailgate should be released and locked open, or completely removed, before tipping starts
 - ✓ Operator must ensure that no pedestrians are in the vicinity of the machine when tipping
 - ✓ All ancillary equipment and tools to be secured when tipping
 - ✓ Tailgate should be released and locked open, or completely removed, before tipping starts
 - ✓ Operator must ensure that no pedestrians are in the vicinity of the machine when tipping
- If fitted with a grab/crane:**
- ✓ Operators must be competent and hold a valid industry recognised competence card – as per BB competency standard
 - ✓ Outriggers must be deployed when lifting duties are being conducted (where applicable)
 - ✓ Must comply with the requirements of the site lift plan
 - ✓ Must know the weights of the loads before lifting